

LED PAR-64 COB RGBW 120W Zoom BK

PAR spot with 120 W RGBW LED with manual zoom



Description:

PAR spotlight with 120 watt RGBW LED and manual zoom

The LED PAR-64 COB is equipped with a powerful 120 W LED (COB) in red, green, blue and white (RGBW). It is ideal for your lighting installation. Thanks to its adjustable PWM frequency, its projection is flicker-free - the spotlight is also suitable for video recording.

The beam angle is manually adjustable from 10° to 40°.

Choose from different dimmer curves and speeds - according to your needs.

Control is via DMX or in stand-alone mode. In auto and music mode you can play three integrated show programs.

You can address and adjust your PAR spotlight via the integrated control unit with 4-digit LED display.

The P-Con connections make it easy to connect up to eight devices together.

CODE : LCG-PL64Z

Weight: 5.00 kg

Length: 0.49 m

Width: 0.37 m

Height: 0.37 m

Features:

- High light output for stage and light installations
- 1 high-performance 120 W RGBW LED (COB)
- Superior color mixing
- Manual beam angle adjustment 10-40°
- Different dimmer curves and speeds selectable
- PWM frequency adjustable 900-25000 Hz (pulse width modulation)
- Strobe effect with adjustable speed
- 9 color presets
- 3 built-in auto and music show programs
- Addressing and setting via control panel with 4-digit LED display

- With color filter frame
- Swivel mounting bracket
- P-Con terminals for power linking up to 8 units
- LED: 1 x COB (chip-on-board) 120 W 4in1 QCL RGBW (homogenous color mix)
- Can be operated in 2/3/4/5/6/10; 6 CH mode
- The device is cooled by temperature-controlled fan
- Controlling by Stand-alone; DMX; Sound to light via Microphone; Master/slave function
- Flicker-free projection

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	140 W
IP classification:	IP20
Protection class:	Class I
Power connection:	Mains input P-Con (blue), mounting version Power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Fuse:	F 2 A
Lamp type:	LED lamp
LED:	1 x COB (chip-on-board) 120 W 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2/3/4/5/6/10
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; Sound to light via Microphone; Master/slave function;
Beam angle:	10 - 40°
Beam angle (1/2 peak):	11 - 35°
Beam angle (1/10 peak):	15 - 48°
Housing color:	Black
Dimension:	Width: 26 cm Depth: 43.5 cm Height: 37.5 cm
Weight:	3.90 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Ecodesign regulation:	Yes
Special product:	Not designed for household room illumination
Purpose:	Show effect lighting