



MINIBEAMER6

LCG-1507/ LED WASH IP65

Specifications

Technical Data

LED Type: 15W RGBWAUV 6in 1 LEDs
LED Count: 7
LED Colors: RGBWAUV
Beam angle: 25°

Control & Effects

DMX mode, Auto Mode, Master slave, Manual mode
DMX Channels: 3 / 6 / 8 / 12 CH
Built-in effect: color mixing, variable color chasing, strobing & fading
Maximum 66 ID setting for easy separately control
Display: LCD
Protocol: USITT DMX-512, RDM
RDM: Bidirectional communication
10 internal programs
10 customize programs
4 different dimming curve
11 kinds of color temperature white
Smart temperature control
Working time record
Key lock for buttons

Connectors

Signal connection: Seetronic IP65 XLR 3-Pin In/Out
Power Input: Seetronic powerCON TRUE1 In/Out

Operating Conditions

Mains voltage: 100-240V AC / 50-60Hz
Power: 105W
Rating: IP65
Maximum ambient temperature: -30°C / 86°F, 50°C / 122°F
Operating Position: Any

Housing Color

Standard color: Black
Material: Aluminum body

Dimensions



Length: 266 mm / 10.5 in
Width: 127 mm / 5.0 in
Height: 266 mm / 10.5 in

Weight

3.4 kg / 7.5 lb



Dimensions



L.C. GROUP | 422, Chemin des Prairies, Joliette, Québec, Canada, J6E 4J8
Tel: (450) 755-6091 | Toll free: (800) 263-6091
www.lc-group.ca | info@lc-group.ca